

Version: Q2 - 2021

North American Standard Product Range

www.garnica.one



garnica

Challenge the ordinary

elegance
birch

Decorative panel with poplar core and birch faces

Glue Type: Interior

Face Grade: Rotary cut B-2 & C-2 (SAP and Natural Color)

Formats (")		1/4*	3/8	1/2	5/8	3/4	1	1 1/4	1 1/2
48.5 x 96.5	No. of plies	5	5	7	7	9	11	15	19
48.5 x 120.5**	Packaging	155	101	77	62	52	38	34	31

* Only in C-4 quality

** Only in C-2 quality

elegance
maple

Decorative panel with poplar core and maple faces

Glue Type: Interior

Face Grade: Rotary cut B-2 & C-2 (SAP and Natural Color)

Formats (")		1/4*	3/8	1/2	5/8	3/4	1	1 1/4	1 1/2**
48.5 x 96.5	No. of plies	5	5	7	7	9	11	15	19
48.5 x 120.5**	Packaging	155	101	77	62	52	38	34	31
60.5 x 96.5**									

* Only in C-4 quality

** Only in C-2 quality

Face Grade: Sliced cut A-1 (SAP and Natural Color)

Formats (")		1/4*	3/8	1/2	5/8	3/4	1
48.5 x 96.5	No. of plies	5	5	7	7	9	11
	Packaging	155	101	77	62	52	38

* Only in C-4 quality

elegance
red oak

Decorative panel with poplar core and red oak faces

Glue Type: Interior

Face Grade: Rotary cut (B-2) & Sliced cut (A-1 & B-1)

Formats (")		1/4	3/8	1/2	5/8	3/4	1	1 1/4*
48.5 x 96.5	No. of plies	5	5	7	7	9	11	15
	Packaging	155	101	77	62	52	38	34

* Only in B-2 (Rotary cut)

elegance
cherry

Decorative panel with poplar core and cherry faces

Glue Type: Interior

Face Grade: Sliced cut (A-1 & B-2)

Formats (")		1/4	3/8	1/2	5/8	3/4	1
48.5 x 96.5	No. of plies	5	5	7	7	9	11
	Packaging	155	101	77	62	52	38

UV All the range available with clear UV finish 1 or 2 sides

CARB Phase 2/TSCA Title VI - NAF and PEFC Controlled Sources
Certifications on demand: **PEFC Certified**

elegance
white oak

Decorative panel with poplar core and white oak faces

Glue Type: Interior

Face Grade: Sliced cut (A-1) & Rift cut (B-2)

Formats (")		1/4	3/8	1/2	5/8	3/4	1
48.5 x 96.5	No. of plies	5	5	7	7	9	11
	Packaging	155	101	77	62	52	38

elegance
walnut

elegance
sapelli

elegance
hickory

elegance
khaya

Decorative panel with poplar core and walnut, sapelli, hickory or khaya faces

Glue Type: Interior

Face Grade: Sliced cut A-1

Formats (")		1/4	3/8	1/2	5/8	3/4	1
48.5 x 96.5	No. of plies	5	5	7	7	9	11
	Packaging	155	101	77	62	52	38



Lightweight poplar plywood from fast-growing European plantations suitable for an infinite number of uses thanks to its exceptional versatility.

efficiency
poplar

**100% sustainable European poplar
lightweight panel**
Glue Type: Interior
Face Grade: B/BB & BB/BB



Formats (")		1/4	3/8	1/2	5/8	3/4	1	1 1/8	1 1/4	1 1/2	1 3/4	2
48.5 x 96.5	No. of plies	5	5	7	7	9	11	11	11	15	17	19
	Packaging	155	101	77	62	52	38	34	31	26	22	19
60.5 x 96.5 48.5 x 120.5 60.5 x 120.5	No. of plies	3	5	7	7	9	11	-	11	15	17	19
	Packaging	155	101	77	62	52	38	-	31	26	22	19

CARB Phase 2/TSCA Title VI - NAF and PEFC Controlled Sources
Certifications on demand: **PEFC Certified, FSC® Mix Credit**

efficiency
hdf

Panel with poplar core and HDF faces
Glue Type: Interior



Formats (")		1/2	5/8	3/4	1	1 1/8	1 1/4	1 1/2	1 3/4	2
48.5 x 96.5	No. of plies	5	7	9	11	11	11	15	17	19
	Packaging	77	62	52	38	34	31	26	22	19
48.5 x 108.5 48.5 x 120.5 60.5 x 96.5 60.5 x 120.5	No. of plies	5	7	9	11	-	11	15	17	19
	Packaging	77	62	52	38	-	31	26	22	19

CARB Phase 2 / TSCA Title VI and PEFC Controlled Sources
Certifications on demand: **PEFC Certified**



**Fireproof plywood modified by using an innovative treatment
that makes the whole panel exceptionally fire-resistant.**

fireshield
building

ASTM E-84 Class A fire-resistant panel
Glue Type: Interior
Face Grade: BB/BB

Formats (")		1/4	3/8	1/2	5/8	3/4	1
49 x 97 49 x 121 61 x 121	No. of plies	5	5	7	9	9	11
	Packaging	155	101	77	62	52	38

CARB Phase 2 / TSCA Title VI and PEFC Controlled Sources
Certifications on demand: **PEFC Certified, FSC® Mix Credit**





Plywood for outdoor use modified by using an innovative treatment that gives the whole panel exceptional durability.



Ultra-durable panel
for outdoor use
Glue Type: Exterior
Face Grade: BB/BB

Formats (")		1/2	3/4
48.5 x 96.5	No. of plies	7	9
60.5 x 120.5	Packaging	77	52



CARB Phase 2 / TSCA Title VI and PEFC Controlled Sources
Certifications on demand: PEFC Certified, FSC® Mix Credit



15 YEAR WARRANTY

Against delamination and fungal
and xylophagous insect attack

+ Info www.duraply.one



deco

Decorative highly-durable panel for use
in demanding humid conditions

Finishes available:

Birch: Rotary cut C-2 (SAP and Natural Color)

Maple: Rotary cut C-2 & Sliced cut A-1 (SAP and Natural Color)

Walnut, Cherry, Sapelli & White Oak: Sliced cut A-1

Glue Type: Interior

Formats (")		1/2	3/4
48.5 x 96.5	No. of plies	7	9
	Packaging	77	52

CARB Phase 2 / TSCA Title VI and PEFC Controlled Sources
Certifications on demand: PEFC Certified



Finish available
on demand

performance

Plywood with premium poplar core with high-quality
interior sheets for more demanding applications.

performance
ultra-smooth

PRM

new
UNIFORM
SURFACE

Premium poplar panel with primed smooth surface
Available with both faces primed and UV maple back
Glue Type: Interior

Formats (")		1/2	3/4
48.5 x 96.5	No. of plies	7	9
60.5 x 96.5	Packaging	77	52
60.5 x 120.5*			

* Only available with primed surfaces

CARB Phase 2 / TSCA Title VI and PEFC Controlled Sources
Certifications on demand: PEFC Certified



performance
poplar

HPL

Premium panel with poplar
core finished with HPL
Glue Type: Interior

Formats (")		1/2	3/4
48 x 96	No. of plies	9	11
	Packaging	77	52

CARB Phase 2/TSCA Title VI - NAF

Standard finishes available:

HPL

White 204 matte
White 204 glossy
White 204 top face
White 753 velvet
White 753 glossy

Black 202 matte
Graphite 1397 velvet
Gray 1411 velvet
Gray 1411 glossy
Barrique Oak 780
American Oak 668

CPL

Bovary Elm E2297
Caledonian Oak A0396
Virginia Oak A1014
Hickory E0138



**ultralight
poplar**

Panel with XPS core
and poplar plywood
Glue Type: Interior
Face Grade: BB/BB

HPL Finish available
on demand

Total thickness (")		5/8	3/4	1	1 1/2	2
48.5 x 96.5	Weight (lbs/panel)	28.5	29.2	30.7	33.7	36.6
48.5 x 120.5						
60.5 x 120.5	Packaging	65	54	40	27	20

Standard plywood panels: 4.5 mm total thickness

CARB Phase 2 / TSCA Title VI and PEFC Controlled Sources
Certifications on demand: PEFC Certified

**ultralight
duraply**

Ultra-durable panel with XPS core
for outdoor use
Glue Type: Exterior
Face Grade: BB/BB

HPL Finish available
on demand

Total thickness (")		5/8	3/4	1	1 1/2	2
48.5 x 96.5	Weight (lbs/panel)	28.5	29.2	30.7	33.7	36.6
48.5 x 96.5						
	Packaging	65	54	40	27	20

Standard plywood panels: 4.5 mm total thickness

CARB Phase 2 / TSCA Title VI and PEFC Controlled Sources
Certifications on demand: PEFC Certified

**ultralight
birch**

**ultralight
maple**

Panel with XPS core, poplar plywood
and birch or maple faces
Glue Type: Interior
Face Grade: Rotary cut C-2 (SAP and Natural Color)

Total thickness (")		5/8	3/4	1	1 1/2	2
48.5 x 96.5	Weight (lbs/panel)	28.5	29.2	30.7	33.7	36.6
48.5 x 96.5						
	Packaging	65	54	40	27	20

Standard plywood panels: 4.5 mm total thickness

CARB Phase 2 / TSCA Title VI and PEFC Controlled Sources
Certifications on demand: PEFC Certified



European Pine plywood sourced from
sustainably-managed plantations.

**laudio
deco**

Decorative European pine plywood
Glue Type: CARB ULEF Phenolic Exterior Glue
Face Grade: A/C

Formats (mm)		11/32	15/32	19/32	23/32
48 x 96	No. of plies	4	5	5	7
	Packaging	107	80	64	53

CE System 2+ and CARB Phase 2 / TSCA Title VI - ULEF
Certifications on demand: PEFC Certified



**We challenge the ordinary
by exploring the limits
of perfection to engineer
the finest plywood for the
most demanding clients.**

The figures included in this file are for information purposes only and have no contractual value. The formats, dimensions, thickness, packaging and plies may vary with no prior notification based on new developments and technological advancements or market needs. The buyer is responsible for deciding whether the Garnica product is suitable for the desired application, and will be required to ensure that the location and way in which it is used are suitable according to the manufacturer's instructions and suggestions, as well as its compliance with current regulations.

Proudly distributed by



UCS Global

1 866 656 3830

Tel 856 693 7571

sales_global@ucsglobal.com

ucsglobal.com

garnica

Challenge the ordinary



Phone:
+34 941 51 23 53



Web:
www.garnica.one



E-mail:
customerserviceusa@garnica.one



Twitter:
@garnicaplywood



Instagram:
@garnicaplywood



YouTube:
Garnica



Linkedin:
Garnica Plywood



Pinterest:
@garnicaplywood

www.garnica.one